

Exam : IBM 000-892

Title : IBM Tivoli Deployment
Professional - Tivoli NetView
Implntn

Update : Demo

1.After uninstalling NetView for Windows, what additional step may be required to complete the uninstall process?

- A.Delete the usr directory.
- B.Reinstall the service pack.
- C.Reinstall the SNMP service.
- D.Delete the NetView server icon from the Tivoli desktop.

Correct:A

2.What is the function of the chktrapd script on NetView for UNIX?

- A.Add new trap configurations.
- B.Identify trapd.log files that exceed a specific size.
- C.Identify possible trap configuration migration errors.
- D.Delete all trap configurations that are no longer supported.

Correct:C

3.What command provides the most comprehensive test for proper operation of the SNMP agent and proper configuration of the SNMP configuration on a NetView machine?

- A./usr/OV/bin/snmpget
- B./usr/OV/bin/snmpctest
- C./usr/OV/bin/snmpnext
- D./usr/OV/bin/snmpwalk

Correct:D

4.In which two situations should a Mid-Level Manager be utilized? (Choose two).

- A.When there is a need for trap filtering.
- B.When several different maps need to be created.
- C.When a map is divided into two or more container objects.
- D.When there are a wide variety of managed network devices.
- E.When there are managed devices beyond a firewall that does not allow ping or SNMP from your NetView Server.

Correct:A E

5.Which two statements are correct about installing the Web Console? (Choose two).

- A.There is no standalone Web Console application for Linux.
- B.The standalone Web Console can be downloaded from the NetView server using a web browser.
- C.If the Web Console standalone client is installed, it should be reinstalled if a NetView fix pack is applied.
- D.The standalone Web Console application must always be downloaded with an included Java Runtime Environment.
- E.A web browser plug-in is required and available for AIX, Solaris, Linux, and Windows platforms to support the NetView Web Console in a browser.

Correct:B C

6.Which factor is a consideration in sizing memory for a NetView Server?

- A.network speed
- B.number of processors
- C.type of operating system
- D.number of interfaces to be managed

Correct:D

7.Which two features are supported in NetView for Linux? (Choose two).

- A.Framework installation
- B.Ruleset Editor
- C.integration with Data Warehouse
- D.Agent Policy Manager
- E.export of snmpCollect data through a RIM interface

Correct:B C

8.Which command tests local TCP/IP configuration?

- A.ovstatus
- B.ping loopback
- C.ping broadcast
- D.ping 255.255.255.255

Correct:B

9.Which step is necessary during the initial design phase of a NetView deployment?

- A.Estimate ovwdb cache size.
- B.Estimate number of operators.
- C.Evaluate name resolution method.
- D.Evaluate need for NetView clients.
- E.All of the above

Correct:E

10.When installing NetView for Windows, which of the three will you be prompted for? (Choose three).

- A.Database type.
- B.The Administrator password.
- C.Path for NetView installation.
- D.Password for the NetView user.
- E.Drive on which to install NetView.
- F.SNMP community names to use as alternate defaults.

Correct:D E F

11.Which action is required during installation of NetView for Windows?

- A.Stop the SNMP service.
- B.Disable the network interface(s).
- C.Define a NetView user account named V?
- D.Define a password for the NetView user account.

Correct:D

12.What optional file contains environmental variables used to control Netview daemons and is sourced before daemon startup?

- A./usr/OV/bin/applsetup
- B./usr/OV/bin/netnsrc.pre
- C./usr/OV/conf/nvsnmp.conf
- D./usr/OV/bin/netnsrc.aux

Correct:B

13.NetView polling is causing excessive load on an SNMP-capable router. Which action may

reduce the problem?

- A. Create a SmartSet for routers.
- B. Increase the ICMP status polling interval.
- C. Change the SNMP community string to read-write.
- D. Reduce the maximum number of routing table entries retrieved.

Correct:D

14. Which daemon must be running for MIB data collections?

- A. nvcold
- B. netmon
- C. collectiond
- D. snmpCollect

Correct:D

15. What must be done in order for traps from a device to be received by NetView?

- A. The MIB-II variable sysTrapDestination in the device's MIB must be set to NetView's IP address.
- B. The device must be configured with NetView's IP address according to the manufacturer's directions.
- C. NetView's SNMP trap configuration program must be run so it can configure the device's trap destination table.
- D. Both of the MIB-II variables sysTrapDestination and sysTrapSeverity in the device's MIB must be set for all traps to be sent to NetView.

Correct:B

16. What is required for NetView Web Consoles to connect to a NetView server?

- A. Run the oww onfigweb command.
- B. The webserver daemon must be running.
- C. The netviewd daemon must be running.
- D. Install a Java compiler on the remote workstations.

Correct:B

17. Which two packets can be sent to an IP address by NetView's status polling mechanism? (Choose two).

- A. TCP Sync packet
- B. UDP Ping packet
- C. ICMP Echo Request packet
- D. SNMP Get packet for sysUpTime
- E. SNMP Get packet for operational status

Correct:C E

18. What are the valid alternative options for the Event Stream node in a rule set?

- A. Pass and Block
- B. Accept and Reject
- C. Enable and Disable
- D. Forward and Return

Correct:A

19. Without the use of scripts, what is one function of a rule set?

- A. to change polling parameters
- B. to add selected objects to the seed file

-
- C.to set default web user security permissions
 - D.to automatically remove events from the events display application

Correct:D

20.What are two ways to recycle the SNMP daemon on AIX? (Choose two).

- A.reset_snmpd
- B.snmpd -restart
- C.refresh -s snmpd
- D.recycle -s snmpd
- E.stopsrc -s snmpd; startsrc -s snmpd

Correct:C E

21.In order to collect SNMP V2 MIB data for performance and thresholding, what configuration steps must be taken?

- A.Modify the snmpCol.conf file.
- B.Use the xnmcollect command.
- C.It is not possible to collect SNMP V2 data.
- D.Use the menu option to collect MIB data for thresholding and performance.

Correct:A

22.What should a NetView administrator do to allow Web Console users to access only a subset of devices contained in the default map?

- A.Hide the subset of devices from specific users.
- B.Set scoping in the Web Console Security menu.
- C.Create an access file in each user home directory.
- D.Set the users?default map access using ovwchmod.

Correct:B

23.Which command can be used to dump current polling schedule (pingWait list) of all devices to a file in NetView for UNIX?

- A.snmpd -p
- B.netmon -a
- C.ovtopodump -rl
- D.xnmsnmpconf -dumpCache

Correct:B

24.Which menu selection directly displays currently configured community names being used by NetView for Windows?

- A.Options > SNMP
- B.Monitor > System
- C.Options > Discovery
- D.Monitor > Community Names

Correct:A

25.What action is required if the NetView Web security settings have been changed?

- A.Run netnrc.
- B.Run ovw -webconfig.
- C.Restart all NetView daemons.
- D.Restart the webserver daemon.

Correct:D

26.Which command should be executed after changing the IP address of the NetView for UNIX server?

- A.ovstart
- B.reset_ci
- C.chmod ipaddr
- D.ovrefresh addr

Correct:B

27.What is one indication that an SNMP enabled device sysObjectID is unknown to NetView?

- A.The device has a cloud symbol on the map.
- B.The device symbol on the map has no bitmap.
- C.The device has an unknown sysObjectID trap in trapd.log.
- D.The device has an unknown sysObjectID trap in the event display.

Correct:B

28.On NetView for UNIX, where is event workspace information saved by default if "Save Environment" is enabled?

- A./usr/OV/registration/C/nvevents
- B./usr/OV/app-defaults/Nvevents file
- C.NvEnvironment/Workspaces file in /usr/OV/conf
- D.NvEnvironment/Workspaces file in the user's home directory

Correct:D

29.By default, how many days does a service need to be down before the service monitor stops monitoring it?

- A.3 days
- B.7 days
- C.30 days
- D.There is no default option for servmon to stop monitoring services.

Correct:B

30.What cannot be configured through the use of the X11 application defaults files?

- A.ovw menu content
- B.whether to display the copyright window
- C.whether the navigation tree should start as an icon
- D.size and location of control desk and its components

Correct:A