

**Test4actual, *100% Accurate Answers!!!***



**Help you pass any IT exam!**

3COM 3M0-250

3Com Certified Enterprise LAN Post-Sales Expert version 1.0

Q&A Demo

1. Which file system command displays the directory entries on a 3Com switch?

- A. dir /all
- B. cd dir /all
- C. display dir
- D. display dir /all
- E. dir display /all
- F. mkdir display /all

Answer: A

2. What is the purpose of the RIP View command network network\_address?

- A. Enables RIP on all switches with this network address
- B. Enables RIP on the switch that is configured with this IP address
- C. Displays all RIP routes associated with this network address or with a subnet of this address
- D. Enables RIP on all interfaces that are configured with this network address or with a subnet of this address

Answer: D

3. Which two are Super-VLAN configuration requirements/limitations on the Switch 8800? (Choose two.)

- A. Up to 64 ports can be assigned to a Super-VLAN
- B. Up to 64 Sub-VLANs can be assigned to a Super-VLAN
- C. ARP, VRRP and DHCP are not supported on Super-VLANs
- D. Sub-VLANs terminate at a router and are isolated at Layer 3
- E. Super-VLANs are assigned an IP address. Sub-VLANs may not be assigned an IP address

Answer: B, E

4. Which Switch 5500 model(s) does not support Distributed Resilient Routing (DRR)?

- A. Switch 5500-EI
- B. Switch 5500-SI
- C. Switch 5500G-EI
- D. All of the above

Answer: B

5. What is the result of the command boot boot-loader file-url?

- A. Reboots the switch using the file-url for the operational code
- B. Updates the switch BootROM with the file-url on the system flash
- C. Reboots the switch fabric only using the file-url for the operational code
- D. Specifies the switch to use file-url for the operational code on the next boot

Answer: D

6 Which two are reasons to use OSPF as your network routing protocol? (Choose two.)

- A. OSPF scales to support larger networks by establishing multiple areas
- B. Although RIP provides faster network convergence than OSPF, OSPF provides greater link reliability

- C.OSPF uses less network bandwidth than RIP by using IP multicast to send advertisements
- D.OSPF updates the network topology by forwarding the entire routing table, minimizing the need for multiple reconfigurations
- E.OSPF only maintains the information on the best path or fastest link, reducing the size of the table and therefore network utilization

Answer: AC

7.You have created a DHCP server group on your switch for improved reliability and redundancy. How do you configure the VLAN interface on the switch to identify the DHCP server group?

- A.Configure all the VLAN interfaces with the DHCP server group IP addresses
- B.Configure the DHCP server group with the primary VLAN interface using the DHCP server group number
- C.Configure the primary VLAN interface with the master DHCP server and all secondary VLAN interfaces with the slave DHCP server
- D.First you must disassociate the VLAN interface from any previous DHCP server group assignment, then configure the DHCP server group with the primary VLAN interface using the IP address of the server

Answer: B

8.Which two methods can be used for day-to-day copying of switch configuration and software files on the Switch 5500/7700/8800? (Choose two.)

- A. USB port with a flash drive
- B. File Transfer Protocol (FTP)
- C. Trivial File Transfer Protocol (TFTP)
- D. Simple Network Management Protocol (SNMP)

Answer: B, C

9.Which Switch 5500 command would display the status of the front panel Ethernet port #13 on switch unit #2?

- A. [ 5500-EI ] display interface e 2/13
- B. [ 5500-EI ] display interface e 2/0/13
- C. [ 5500-EI ] display interface e 2/1/13
- D. [ 5500-EI ] display interface e 13/0/2

Answer: B

10.What is the reason to connect the p port on the bottom Switch 5500 in the stack to the down port of the top Switch 5500 in the same stack?

- A. Reliability - creates a resilient topology
- B. Security - prevents an unauthorized user from connecting to the switch stack
- C. Performance - creates the 48-Gbps eXpandable Resilient Networking (XRN) Fabric
- D. Management - enables Distributed Resilient Routing (DRR) on the Switch 5500-SI

Answer: A